

# TYPE APPROVAL CERTIFICATE

Certificate No: **TAA00001B8**Revision No: 2

т	h	i٩	: is	to	CP	rtify	, -
		13	, i a	···	66		=

That the Safety Unit for Rotating Machinery

with type designation(s)

Oil Mist Detection System VISATRON VN301plus / VN301plus Ex

Issued to

# Schaller Automation Industrielle Automationstechnik GmbH & Co KG Blieskastel, Saarland, Germany

is found to comply with

DNV local station: Augsburg

DNV rules for classification - Ships, offshore units, and high speed and light craft

Application :					
Location classes can be found on page 2.					
Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.					
Issued at Hamburg on 2022-06-13					
This Certificate is valid until 2027-06-12.	for <b>DNV</b>				

Approval Engineer: Didier Girardin

Joannis Papanuskas

Head of Section

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 251 Revision: 2021-03 www.dnv.com Page 1 of 4

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: 262.1-013001-4 Certificate No: TAA00001B8

Revision No: 2

# **Product description**

The Oil Mist Detector (OMD) VISATRON® VN301<sup>plus</sup> / VN301<sup>plus</sup> Ex system made by Schaller Automation Industrielle Automationstechnik GmbH & Co KG is a safety system protecting reciprocating internal combustion engines against oil mist explosion, caused by spontaneously occurring oil mist.

Type 1)	Location classes					
	Temperature	Humidity	Vibration	EMC	Enclosure	SW <sup>2)</sup>
VN301 plus - CU (Central Unit)	В	В	В	Α	B (IP65)	1.21
VN301 plus - V	В	В	В	Α	B (IP65)	1.17
VN301 plus - H	В	В	В	Α	B (IP65)	1.17
VN301 plus Ex - V	В	В	В	Α	B (IP65)	1.17
VN301 plus Ex- H	В	В	В	Α	B (IP65)	1.17
VN301 plus – Left Side	В	В	В	Α	B (IP65)	1.17
VN301 plus Ex - Left Side	В	В	В	Α	B (IP65)	1.17

Note:

- 1) Connection type: V (vertical), H (horizontal)
- 2) Type approved software version 1.xx

#### Place of manufacture

Schaller Automation Industrielle Automationstechnik GmbH & Co KG,

Blieskastel,

Federal Republic of Germany

# Application/Limitation

The Type Approval covers hardware and released software version listed under Product description.

- 1. Ex-certification is not covered by this certificate. Application in hazardous area to be approved in each case according to the Rules and Ex-Certification / Special Condition for Safe Use listed in valid Ex-certificate issued by a notified/recognized Certification Body.
- 2. List of control & monitored points (including alarms, shutdowns, set points, etc.) shall be according to the engine's intended function (propulsion, auxiliary genset, emergency genset, etc.) and shall comply with the vessel's main class requirements in DNV GL Rules for Ships, HS, LC and NSC Pt.4 Ch.3 Sec.1 Table 9, 10, 11 and, if Ship Rules and E0 notation apply, Pt.6 Ch.2 Sec.2 Tables 4 and 8.

#### Product certificate

As long as the units are covered by the Type Approval, a product certificate according to Pt.4 Ch.9 Sec.1 A 202 will **not be** required. Correct configuration and set up for each delivery to be tested as part of switchboard functional testing and during commissioning after installation.

The following documentation of the actual application is to be submitted for approval in each case:

- Reference to this Type Approval Certificate
- System block diagram
- Power supply arrangement (may be part of the System block diagram)
- Confirmation that List of control & monitored points is like stated in Application/Limitation point 2

# Clause for application software control

All changes in software are to be recorded as long as the system is in use on board. The records of all changes are to be forwarded to DNV GL for evaluation and approval.

Major changes in the software are to be approved before being installed in the computer.

A Certification of Application Functions may be required for the particular vessel.

#### Type Approval documentation

See ANNEX

#### **Tests carried out**

Applicable tests according to Class Guideline DNV-CG-0339, August 2021 Applicable tests according to IACS UR M67 (Rev.2 Feb 2015)

Functional type test at Schaller Automation Industrielle Automationstechnik GmbH & Co KG, Blieskastel, Federal Republic of Germany, 2012-07-18

Form code: TA 251 Revision: 2021-03 www.dnv.com Page 2 of 4



Job ld: 262.1-013001-4 Certificate No: TAA00001B8

Revision No: 2

#### Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

**END OF CERTIFICATE** 

Form code: TA 251 Revision: 2021-03 www.dnv.com Page 3 of 4



Job Id: **262.1-013001-4** Certificate No: **TAA00001B8** 

Revision No: 2

# **ANNEX**

Hidden

_							4.0
Tec	hn	ical	ld	വ	Ime	ntaد	ition

Document name:	Document no.	Rev.	Date
Dim. Drawing VN301 plus CPU	DC180403 02	002	2013-07-04
Dim. Drawing VN301 plus Sensor unit	DC180401 02	004	2014-09-24
Sensor Unit, Material Listing DC180405	DC180405 02	003	2014-09-24
Data sheets			
Circuit diagram Connection board	210970	007	2014-04-10
Circuit diagram CPU board	210971	007	2014-12-14
Circuit diagram VN301 plus sensor unit	1000006	004	2012-06-29
Circuit diagram VN301 plus sensor transmitter	1000032	004	2016-03-07
Circuit diagram VN301 plus EX sensor unit	1000048	003	2012-09-10
Process-Instruction: Software	VA 7.3 04e	V11	2021-09-24

EMC and ENV tests reports			
Document name:	Document no.	Rev.	Date
Test report CETECOM (EMC)	1-4083/11-01-02		2012-03-02
Test report CETECOM (ENV)	1-4083/11-01-03		2012-03-13
Test report CETECOM (IP)	1-4083/11-01-05		2012-03-13
Test report CETECOM (EMC)	1-5141-12-01-03		2012-07-31
Test report CETECOM (ENV)	1-5141/12-01-02		2012-08-08
Test report GSSO			2012-03-15
Operation Manual Visatron® VN301plus/VN301plusEX		1-2	2015-04

Document name:	Rev.	Date
OMD Function Test IACS UR-M67 Rev2 (Test Report)	-	2017-03-22
OMD Function Test IACS UR-M67 Rev-2 (Annex)	_	2017-03-22

Compliancy to IACS E10 Rev.07 Document name:

Document name:	Rev.	Date
9917_05122019_VN301plus	1.0	06.12.2019

Form code: TA 251 Revision: 2021-03 www.dnv.com Page 4 of 4